


ネジ式タイプのポリプロピレン継手


使用温度 0℃～+80℃ 常温圧力 6kg/cm²、+80℃の圧力 4kg/cm²

P.Pエルボ




サイズ	A	B
½Rc	30.0	43.0
¾Rc	37.0	49.5
1Rc	45.0	60.5
1¼Rc	53.0	71.5
1½Rc	64.0	81.0
2Rc	76.0	97.0

P.Pニップル




サイズ	A	B	内径
¼R	33.5	17.0	7.0
⅜R	37.5	21.0	8.6
½R	45.0	22.0	12.0
¾R	49.0	27.0	16.3
1R	57.0	36.0	22.3
1¼R	62.0	46.0	31.0
1½R	67.0	50.0	36.0
2R	76.0	65.0	45.5

P.Pチーズ



サイズ	A	B	C
½Rc	55.0	43.0	30.0
¾Rc	65.0	49.5	37.0
1Rc	74.5	60.5	45.0
1¼Rc	88.0	71.5	53.0
1½Rc	99.5	81.5	64.0
2Rc	120.0	98.5	76.0


P.Pブッシング



サイズ	A	B	
⅜R×¼Rc	33.0	22.0	
½R×⅜Rc	38.0	28.0	
¾R×½Rc	41.2	35.5	
1R×¾Rc	44.0	37.0	
1¼R×1Rc	50.0	45.0	
1½R×1¼Rc	55.0	55.0	丸タイプ※
2R×1½Rc	60.0	64.0	丸タイプ※



※印は注文製作品です。

P.Pソケット




サイズ	A	B
¼Rc	32.5	20.5
⅜Rc	33.0	26.0
½Rc	35.0	31.0
¾Rc	38.8	38.0
1Rc	44.5	46.0
1¼Rc	50.0	53.0
1½Rc	55.0	64.0
2Rc	65.0	76.0

P.Pキャップ




サイズ	A	B
½Rc	20.3	36.4
¾Rc	23.6	41.4
1Rc	25.5	49.0
1¼Rc	29.0	55.0
1½Rc	31.0	60.0
2Rc	36.0	81.0

P.Pユニオン





サイズ	A	B	C
½Rc	47.3	47.0	27.0
¾Rc	53.0	56.0	36.0
1Rc	58.0	67.0	41.0
1¼Rc	65.0	81.0	51.0
1½Rc	77.0	96.0	64.0
2Rc	89.0	126.0	80.0

P.Pプラグ



サイズ	A	B
½R	24.6	26.4
¾R	27.0	35.0
1R	31.0	40.0
1¼R	35.0	50.0
1½R	36.0	60.0
2R	42.0	75.0


P.P合フランジ



ポリプロピレン製 10Kタイプ合フランジ

サイズ	A	B	C	
¾Rc	100.0	75.0	19.0	10Kタイプ
1Rc	125.0	90.0	19.0	//
1¼Rc	135.0	100.0	21.0	//
1½Rc	140.0	105.0	21.0	//
2Rc	155.0	120.0	21.0	//

P.P竹の子



サイズ	A	B	C	D
¾	60.5	20.5	37.0	28.3
1	71.8	26.0	46.0	36.5
1¼	80.5	32.0	50.0	46.5
1½	90.0	40.0	59.5	51.0
2	97.0	50.8	64.0	61.5
2½	142.0	64.0	92.0	80.0
3	161.0	76.5	107.0	93.0

※予告なしに品質・性能・改善のため寸法を変更する事があります。